

PROCESSING CAPABILITIES



Low Carbon, High Carbon, HSLA, Alloy, Ferritic Stainless, Others		Gauge	Width	Length	ID	OD	Max Weight	Condition
Combination Reversing Mill	Inbound	.017/.250"	24"- 60"	Coil	24" Only	36"-74"	72,000#	HR P&O and CR
	Outbound	.015/.250"	24"- 60"	Coil	24" Only	36"-74"	72,000#	Cold Reduced, Temper Rolled, Skin Pass

Low Carbon, High Carbon, HSLA, Alloy, Ferritic Stainless, Others		Gauge	Width	Length	ID	OD	Max Weight	Temperature
Hydrogen Anneal	Inbound	.015" Min	14" Min	Coil	24" Min	44"-72"	60,000#	Up to 1562° F (850° C)
	Outbound	.015" Min	14" Min	Coil	24" Min	44"-72"	60,000#	

Low Carbon, High Carbon, HSLA, Alloy, Ferritic Stainless, Others		Gauge	Width	Length	ID	OD	Max Weight	Condition
Pickler	Inbound	.060/.500"	24"- 72"	350' Min	20"- 32"	44"-76"	80,000#	HR
	Outbound	.060/.500"	72" Max up to .375" 60" Max up to .500" 48" Max up to .625"	Coil	24" Only	44"-76"	60,000#	Oil or Dry
Heavy Gauge Slitter	Inbound	.125/.700"	15"-76"	Coil	20"- 32"	36"- 80"	80,000#	HR or HR P&O
	Outbound	.125/.700"	3"-72"	Coil	24" or 28"	36"-76"	80,000#	3"- 6" Widths by Inquiry
Light Gauge Slitter	Inbound	.060/.375"	15"-76"	Coil	20"- 32"	36"-76"	60,000#	HR or HR P&O
	Outbound	.060/.375"	3"-72"	Coil	20", 24" or 30"	36"-74"	60,000#	3"- 4" Widths by Inquiry
Heavy Gauge Leveler	Inbound	.165/.565"	24"- 96"	Coil	20"- 32"	36"-74"	80,000#	HR or HR P&O
	Outbound	.165/.565"	24"- 96"	60"- 480"	N/A	N/A	40,000# Bundle	Other Lengths by Inquiry
Light Gauge Leveler	Inbound	.060/.250"	24"-74"	Coil	20"- 32"	36"-74"	80,000#	HR or HR P&O
	Outbound	.060/.250"	24"-74"	60"- 360"	N/A	N/A	40,000# Bundle	Other Lengths by Inquiry
Narrow Width Leveler	Inbound	.125/.500"	6"-24"	Coil	24" or 28"	30"-72"	20,000#	HR or HR P&O
	Outbound	.125/.500"	6"-24"	60"- 480"	N/A	N/A	20,000# Bundle	Other Lengths by Inquiry